

DS-KD8003Y-IME2/NS
Two Wire Main Unit

The KD8 series 2-wire modular door station is designed with stainless steel, whose appearance is simple and texture is great, which helps to provide a safety environment with high resolution image by high resolution camera. According to different scenarios, you can choose different sub modules to extend the device functions, such as display module, signing module, button module, card presenting module, etc., which is suitable for intercom and access control requirements. You can also choose different Hikvision's brackets, satisfying different installation methods, such as surface mounting, flush mounting, etc. The device can also power up to 2 door locks directly, which is safe and easy for installation and deployment. It is suitable for the scenarios of apartment, office, construction site, etc.

- 2-Wire main unit of modular door station
- 2 MP fisheye Camera with IR Supplement
- Two-lock control
- IP65 protection level
- Convenient configuration via Web remotely
- Directly provide 12 V, 500 mA power output for one electronic lock without additional power supply
- Stainless Steel high quality material

▪ Specification


| System parameters | |
|--------------------------------|--|
| Operation system | Embedded Linux operation system |
| ROM | 32 MB |
| RAM | 256 MB |
| Processor | Embedded Processor |
| Display parameters | |
| Screen size | / |
| Operation method | / |
| Type | / |
| Resolution | / |
| Video parameters | |
| Lens | 1 |
| Resolution | 2 MP |
| FOV | Horizontal: 146°, Vertical: 82° |
| Wide dynamic range (WDR) | Support |
| Supplement light | IR light, up to 3 m |
| Video compression standard | H.264; h.265; MJPEG |
| Audio parameters | |
| Audio input | 1 Built-in omnidirectional microphone |
| Audio compression standard | G.711 U、 G.711 A、 Opus、 AAC-LD、 AAC-LC、 G.726、 G.722.1 |
| Audio output | 1 built-in loudspeaker |
| Audio compression bitrate | 64 Kbps |
| Audio quality | Noise suppression and echo cancellation |
| Volume adjustment | Adjustable |
| Capacity | |
| User capacity | 2000 |
| Face capacity | NA |
| Fingerprint capacity | / |
| Message capacity | / |
| Linked indoor station capacity | 500 |
| Sub door station capacity | 16 |
| Network parameters | |
| Network protocol | ipv6、 onvif |
| Wi-Fi | / |
| Bluetooth | / |
| 3G/4G | / |
| Device interfaces | |
| Alarm input | 4 (2 exit buttons and 2 door contacts by default) |
| TAMPER | 1 |
| Exit button | 2 (2 for lock control) |
| RS-485 | 1 (1 for Hikvision's sub module communication) |
| USB | NA |
| Wiegand | NA |
| TF card | NA |

| | |
|-------------------------|---|
| Alarm output | NA |
| Lock control | 2 relays, Max. to 30 VDC, 2 A |
| Door contact input | 2 |
| Two-Wire IP interface | NA |
| General | |
| Button | / |
| Installation | Surface mounting, flush mounting |
| Indicator | / |
| Weight | Net weight: 0.425 kg Gross weight: 0.600 kg |
| Protective level | IP65 |
| Working temperature | -40 °C to 60 °C (-40 °F to 140 °F) |
| Dimension (W × H × D) | 100 mm × 98 mm × 42 mm |
| Battery | / |
| Power supply | Powered by KAD704Y or KAD706Y series distributor |
| Application environment | Outdoor |
| Power consumption | ≤ 4 W |
| Language | English, Arabic, European French, Russian, European Spanish, Latin American Spanish, Italian, German, Polish, Turkish, Portuguese, Brazilian Portuguese, Uzbek, Kazakh, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Lithuanian, Estonian, Latvian, Norwegian, Danish, Slovenian, Slovak, Hebrew, Swedish, Finnish, Mongolian, Vietnamese, Traditional Chinese (Taiwan), Latin American Spanish |

▪ Available Model

DS-KD8003Y-IME2/NS

▪ Dimension



Unit:mm [inch]

| | |
|-------|-----|
| SCALE | 1:1 |
|-------|-----|

▪ **Accessory**

▪ **Optional**

| DS-KD-IN | DS-KD-BK | DS-KD-M | DS-KD-E | DS-KD-DIS |
|------------|-----------------|-----------------|-----------------|--------------|
| | | | | |
| DS-KD-INFO | DS-KABD8003-RS1 | DS-KABD8003-RS2 | DS-KABD8003-RS3 | DS-KD-ACF1/S |

| | | | | |
|---|---|---|--|---|
|  |  |  |  |  |
| DS-KD-ACF2/S | DS-KD-ACF3/S | DS-KD-ACW1/S | DS-KD-ACW2/S | DS-KD-ACW3/S |
|  |  |  |  |  |
| DS-KD-KK/S | DS-KD-KP/S | DS-KD-TDM | DS-KD-TDE | DS-KABD8003-RS1/S |
|  |  |  |  |  |
| DS-KABD8003-RS2/S | DS-KABD8003-RS3/S | DS-KAD706Y-P | DS-KD-K12 | DS-KD-MFB |
|  |  |  |  |  |
| DS-KD-MFB/S | | | | |
|  | | | | |

See Far, Go Further



www.hikvision.com
support@hikvision.com

